









EXHAUST FAN with LIGHT COMPARISON CHART



																
CFM	50	50	70	70	70	70	70	70	70	70	70	100	100	100	80	100
Model	ASLC50	ASF50	ASLC70	ASF70	DRLC701	DRLC702	DRLC703	DRLC709	AKLC701	AKLC702	AKLC703	AK863L	AK864L	AK100L	AKF80LS	AKF100LS
Builder Grade, meets minimum requirements. Lowest initial cost, short duct runs only	X	X	X	X												
Elevated Sound			X	X					X							
Moderate Sound	X	X			X	X	X	X				X	X			
Quiet: 2.5 Sones and less									X	X	X			X		X
Very Quiet: 1.0 Sone and less															X	
Main Light	100 watt	26 watt	100 watt	26 watt	2 - 60 watt	2 - 60 watt	2 - 60 watt	2 - 60 watt	2 - 60 watt	2 - 60 watt	2 - 60 watt	100 watt	100 watt	100 watt	26 watt	26 watt
Night Light												7 watt		7 watt	4 watt	4 watt
California Title 24 Compliant		X		X											X	X
Duct Size	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"	4"
Spring Loaded Backdraft Damper															X	X
Suitable for longer duct runs									X	X	X	X	X	X	X	X
Light Lens	plastic	plastic	plastic	plastic	glass	glass	glass	glass	glass	glass	glass	glass	glass	glass	glass	glass
Finish	white	white	white	white	bronze	nickel	white	brass	bronze	nickel	white	white	white	white	white	white
Continuous Operation					X	X	X	X	X	X	X	X	X	X	X	X
ENERGY STAR®															X	X
High Efficiency Motor									X	X	X	X	X	X	X	X