




SPECIFICATIONS  
**BFQ90**  
 EXHAUST FANS

**HVI** 2100  
 CERTIFIED **90 CFM/2.5 Sones @ 0.10" SP.**



- Grill**  
 White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 10" x 10".
- Blower Wheel**  
 One piece polymeric wheel 5<sup>1</sup>/<sub>8</sub>" diameter, 2<sup>3</sup>/<sub>8</sub>" wide, with 48 fins.
- Motor**  
 Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, thermally protected, suitable for continuous operation. Rated 120 volts, 60 hz.
- Fan Housing**  
 PC/ABS polymeric, dimensions 8<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>8</sub>" x 4<sup>3</sup>/<sub>4</sub>".
- Duct Collar**  
 Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.
- Ventilating Area**  
 For bathrooms up to 90 sq. ft. For other rooms up to 115 sq. ft.
- Single Pack Shipping Info**  
 Box Dim: 11" x 12" x 6"  
 UPC: 0-8316220901-6  
 Shipping Weight: 5<sup>1</sup>/<sub>4</sub> lbs.

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.



- Unit Mounting**  
 Designed to mount in ceilings with at least 6" of clearance. The unit is mounted directly to the joist using a separate lock-in bracket (included with unit). The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 8<sup>1</sup>/<sub>2</sub>" x 9<sup>1</sup>/<sub>8</sub>".

**EXPANDED PERFORMANCE**

	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
<b>Air Flow - CFM</b>	101	95	90	88	85	81	74	2.5	1375	50	0.5

<b>PROJECT</b>							<b>ARCHITECT</b>				
<b>LOCATION</b>							<b>ENGINEER</b>				
<b>CONTRACTOR</b>							<b>SUBMITTED BY</b>			<b>DATE</b>	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



**Air King:** 820 Lincoln Avenue  
 West Chester, Pennsylvania 19380-4466  
 Tel: (610) 692-7400 • 877-304-3785  
 Fax: (610) 696-8048