

SPECIFICATIONS



130 CFM/<0.3 Sones @ 0.10" SP. 112 CFM @ 0.25 SP. (Boost) 50 CFM/<0.3 Sones @ 0.10" SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 17" x 157/8".

Blower Wheel

Balanced polymeric dual inlet blower wheel secured in place using a hex nut.

Motor

Enclosed 4 pole high efficiency, permanently split capacitor motor (PSC); life time lubrication, suitable for continuous operation. Rated 115/120 volts, 60 Hz.

Fan Housing

23 gauge galvanized steel housing. Fan housing dimensions: 12⁷/8"x 12³/4"x 9⁷/8".

Humidity Sensor

Integrated humidity sensor automatically turns fan to high speed until the desired humidity level is reached.


6" round, zinc plated metal collar adapter, 6" spring loaded and gasketed aluminum backdraft damper.

Electrical Connections

0.5" electrical knockouts provided. Easy wiring access via either internal or external wiring compartment cover.

Liahtina

Electronic Quick Start Ballast - rated 26 Watt. Includes 26 watt, Quad 4 pin PL lamp. 4 watt night light (night light bulb not included). TWO SPEED EXHAUST FAN



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.





Unit Mounting

The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 131/8" x 13". The housing will mount either between 16" or 24" on center joists, using the 2 supplied housing mounting brackets. The housing mounting brackets can be adapted for overhead mounting (hardware not provided). The unit is provided with an optionally installed ceiling flange to ensure proper building infiltration rates are maintained and that no air leaks occur between the fan housing and ceiling cutout.

EXPANDED PERFORMANCE											
								Sones	Fan Speed	Maximum	Full Load
	Static Pressure (inches of w.g.)							@ .1 SP	RPM	Fan Watts	Amps
	0	0.1	0.15	0.2	0.25*	0.3	0.35				
Air Flow - CFM (High Speed)	149	130	119	107	91/112	79	62	< 0.3	783	37.0	0.7
Air Flow - CFM (Low Speed)	81	50	33	16	-	-	-	< 0.3	715		

* Ronet engad provides 112 CFM @ 25 Static Proceure 0.6 cones

PROJECT							ARCHITECT				
LOCATION							ENGINEER				
CONTRACTOR							SUBMITTED BY DATE				
FAN MO Number Num	DEL MBER	СҒМ	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		







Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048

Updated 2-16 Specifications subject to change without notice