





High Speed 300 CFM/4.5 Sones @ 0.10" SP. Medium Speed 200 CFM/2.5 Sones @ 0.10" SP. Low Speed 140 CFM/0.7 Sones @ 0.10" SP.

Dimensions

Overall bottom projection - 11" Height -11" Width - 28" (for 30" canopy)

Body

Galvanized steel body with stainless steel fascia.Install at least 24" above the cooking surface.

Lighting

Uses 2 - 18 watt GU24 self ballasted lamps (included).

Ducting

Vertical ducting: 6" round ducting with all metal outlet adapterand back draft damper

Filters


Aluminum grease filters (included).

Blower

3 speed, permanently split capacitor motor. Rated 120 volts, 60 hz. with a dual inlet, electronically balanced polymetric centrifugal blower wheel

Cut Out Opening Size

Width 26%" Depth - 10"



EXPANDED PERFORMANCE											
		Stati	c Pressure	e (inches d	Sones	Fan Speed	Power				
Air Flow - CFM	0	0.1	0.15	0.25	0.3	0.375	@ .1 SP	RPM	Watts	Amps	
High Speed	315	300	292	271	259	238	4.5	1490	87.3	1.1	
Medium Speed	207	200	196	185	178	163	2.5	1335	65.6	1.1	
Low Speed	148	140	134	119	109	92	0.7	1080	65.6	1.1	

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	







Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048

Specifications subject to change without notice. Updated 11-15