



107/8"

6'



90 CFM/0.8 Sones @ 0.10" SP. 65 CFM @ 0.25 SP.

• <u>Grill</u>

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - $11" \times 13\%$ ".

Blower Wheel

Balanced polymeric dual inlet blower wheel $5^{13/32}$ " dia. x 4" depth, 30 paddles, secured in place using 8M hex nut.

Motor

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubrication, suitable for continuous operation. Motor bearings - ball. Rated 115/120 volts, 60 Hz.

• Fan Housing

23 gauge galvanized steel housing. Overall dimensions 10^{7} /s" x 9^{3} /s" x 7^{7} /s".

• Duct Collar

Plastic collar for 6" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 90 sq. ft. For other rooms up to 115 sq. ft.

Electrical Connections

• Single Pack Shipping Info

Box Dim: 16" x 14³/₈" x 9⁷/₈" UPC: 0-8316294102-2 Shipping Weight: 12.5 lbs. Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

77/8"

9³/8"


133/4



• Unit Mounting

The housing will mount in ceilings with at least 8" of clearence and through drywall thickness up to $\frac{3}{4}$ ", with a rough-in opening of 11" x 9½". The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE											
	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.2	0.25	0.3	0.35				
Air Flow - CFM	99	96	90	75	65	56	54	0.8	881	25.7	0.3



Specifications subject to change without notice