



[®] 2100 SP. 90 CFM/1.5 Sones @ 0.10" SP. 75 CFM @ 0.25 SP.

• <u>Grill</u>

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - $11" \times 13\%"$.

• Blower Wheel

One piece polymeric centrifugal blower wheel, $5^{7}\!\!/_{32}$ " diameter, $2^{29}\!\!/_{32}$ " wide, with 30 paddles.

• Motor

Heavy duty, permanently split capacitor, plug-in, 4 pole motor, life time lubrication, suitable for continuous operation. Rated 120 volts, 60 hz.

• Fan Housing

23 gauge galvanized steel housing. Dimensions: 10^{7} /s" x 9^{3} /s" x 7^{7} /s".

• Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

<u>Ventilating Area</u>

For bathrooms up to 90 sq. ft. For other rooms up to 115 sq. ft.

• Electrical Connections

1/2" electrical knockouts provided.

Single Pack Shipping Info

Box Dim Box Dim: 16" x 14%" x 9%" UPC: 0-8316229001-4 Shipping Weight: 12 lbs.

Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

77/8"

9³/₈"

13³/₄



107/8"

4"

• Unit Mounting

The housing will mount in ceilings with at least 8" of clearence and through drywall thickness up to $\frac{3}{4}$ ", with a rough-in opening of 11" x 9½". The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

EXPANDED PERFORMANCE											
	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Maximum Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	97	93	90	89	87	84	75	1.5	1050	25.4	0.3

