





100 CFM/2.0 Sones @ 0.10" SP. 83 CFM @ 0.25" SP.

Grill

White, polymeric grill secured in place with torsion springs; easily removed if necessary, dimensions - 11" x 133/4". Moonstone glass lens.

Blower Wheel

Balanced polymeric dual inlet blower wheel $5^{1/4}$ " dia. x $2^{7/8}$ " depth, 30 paddles, secured in place via press fit.

Motor

Enclosed 4 pole electronically balanced permanently split capacitor motor (PSC); life time lubricated, suitable for continuous operation. Motor bearings - ball. Rated 115/120 volts, 60 Hz.

Fan Housing

23 gauge galvanized steel housing. Overall dimensions 10^{7} /s" x 9^{3} /s" x 7^{7} /s".

Duct Collar

Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 100 sq. ft. For other rooms up to 125 sq. ft.

Electrical Connections

 $\slash\!\!\!/_2$ " electrical knockouts provided. Easy wiring access via either internal or external wiring compartment cover.

Lighting

Dimmable LED Lamp rated 8.5 Watts 800 Lumens 94 Lumens/Watt, 3000K. California Title 24 and JA8 compliant.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

13³/₄¹





Unit Mounting

The housing will mount in ceilings with at least 8" of clearance and through drywall thickness up to $^{3}/_{4}$ ", with a rough-in opening of 11" x 9½". Rated for ceilings insulated to R-40. The housing will mount either between 16" or 24" on center joists, using the 4 supplied housing mounting rails. The housing mounting rails can be adapted for overhead mounting (hardware not provided).

Single Pack Shipping Info

Box Dim: 16" x 143/8" x 97/8" UPC: 0-8316294081-0 Shipping Weight: 13.6 lbs.

| EXPANDED PERFORMANCE | | | | | | | | | | | |
|----------------------|----------------------------------|-----|-----|------|-----|------|-------|-------|-----------|-----------|------|
| | | | | | | | | Sones | Fan Speed | Maximum | |
| | Static Pressure (inches of w.g.) | | | | | | | | RPM | Fan Watts | Amps |
| | 0 | 0.5 | 0.1 | 0.15 | 0.2 | 0.25 | 0.375 | | | | |
| Air Flow - CFM | 108 | 104 | 100 | 95 | 90 | 83 | 70 | 2.0 | 1182 | 26.5 | 0.60 |

| PROJECT | | | | | | ARCHITECT | | | | |
|----------------------------|-----|------------|-----|-------|------|-----------|-------|---------------------------------|--|--|
| LOCATION | | | | | | ENGINEER | | | | |
| CONTRACTOR | | | | | | SUBMITT | ED BY | DATE | | |
| FAN MODEL Number Number | CFM | IN W.G. | RPM | WATTS | AMPS | SONES | QTY | OPTIONAL EQUIPMENT & REMARKS | | |
| | | | | | | | | | | |







U.S.: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048

Canada:

Brampton, Ontario Tel: 905-456-2033

Updated 11-23

Specifications subject to change without notice.