



SPECIFICATIONS

FS50

EXHAUST FAN

50 CFM/3.0 Sones @ 0.10" SP.

- Grill**

Cold rolled steel, powder coated white.

- Blower Wheel**

One piece polymeric wheel, 4 1/2" diameter, 1" wide, with 10 fins.

- Motor**

Single coil plug-in, two pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz.

Contractor Pack (Motor/BladeGrill) Model: FA50TR*

- Fan Housing**

24 gauge galvanized steel housing, dimensions 7 3/8" x 7 9/16" x 6".

Contractor Pack Model: AKFH1*

- Duct Collar**

Metal collar for 3" duct connection, comes complete with built in back draft damper.

- Optional Damper**


Blanket - Non-asbestos, ceramic blanket

Fusible Link - Replaceable, 165°F standard

Classification - CUL Listed 555C and 263. California State Marshall classification for 3 hour fire damper rating. California State Marshall listing number 3226-1722:0110.

Contractor Pack Model: AKFD1R*

* Sold in packs of 4. All three parts (housing, damper, motor/blade/grill) must be purchased and used together to make a complete unit.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

- Unit Mounting**

FS50 is centered between joists (with 16" centers) using hanging brackets. The housing will mount through drywall thickness up to 3/4", with a rough-in opening of 7 1/2" x 7 3/4".

- Ventilating Area**

For bathrooms up to 50 sq. ft. For other rooms up to 60 sq. ft.

EXPANDED PERFORMANCE

	Static Pressure (inches of w.g.)							Sones @ .1 SP	Fan Speed RPM	Power Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	55	53	50	49	47	44	39	3.0	2125	48.0	0.9

PROJECT		ARCHITECT									
LOCATION		ENGINEER									
CONTRACTOR		SUBMITTED BY									
FAN NUMBER	MODEL NUMBER	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS		



U.S.: 820 Lincoln Avenue
West Chester, Pennsylvania 19380-4466
Tel: (610) 692-7400 • 877-304-3785
Fax: (610) 696-8048

Canada:
Bolton, Ontario
Tel: 905-456-2033